

**(19) World Intellectual Property Organization
International Bureau**



(43) International Publication Date
2 March 2006 (02.03.2006)

PCT

(10) International Publication Number
WO 2006/022711 A1

- (51) **International Patent Classification:** **B29C 35/04,**
B29D 30/06

(21) **International Application Number:**
PCT/US2004/026308

(22) **International Filing Date:** 13 August 2004 (13.08.2004)

(25) **Filing Language:** English

(26) **Publication Language:** English

(71) **Applicant (for all designated States except US):** MICHE-
LIN NORTH AMERICA, INC. [FR/US]; 515 Michelin
Road, Greenville, SC 29602 (US).

(72) **Inventors:** YOUNG, Robert; 105 Lombardy Court,
Simpsonville, SC 29681 (US). CHRISTOPHER, Nor-
man; 290 Quail Hollow Road, Fountain Inn, SC 29644
(US). MANUEL, Stephen; 255 Red Maple Road, Flat
Rock, NC 28731 (US).


(74) **Agent:** WILLIAMS, Tim, F.; Dority & Manning, P.A.,
P.O. Box 1449, Greenville, SC 29602 (US).

(81) **Designated States (unless otherwise indicated, for every
kind of national protection available):** AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) **Designated States (unless otherwise indicated, for every
kind of regional protection available):** ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE,
SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: AUTOMATIC PRESSURE AND TEMPERATURE CONTROL APPARATUS AND METHOD FOR CURING TIRE ASSEMBLIES



(57) Abstract: An automatic pressure and temperature control apparatus and method for use in curing tire assemblies (50) including retread tire assemblies is provided. Using water as a heating medium, a new process control method and apparatus utilize an expansion tank if the measured water pressure is below a set-point pressure, allowing a more precise control of process variables during steady state conditions such that heat transfer is improved and the undesirable formation of steam is eliminated. Existing processes and equipment for curing tire assemblies can be modified, using the teaching disclosed herein, to implement and achieve the benefits of the present invention.

WO 2006/022711 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.